

BEST 5K series to STANLEY Commercial Hardware QTL200 series Conversion Chart:

Series	Core Housing	Function Code	Lever Style	Trim Style	Strike Package	Finish	Options
5K	0 - Keyless 6 - 6-pin non-IC cylinder 7 - 7-pin IC housing	A - Entrance D - Storeroom L - Privacy N - Passage R - Classroom 1DT - Dummy Trim	14 - Curved Return 15 - Contour Angle Return	C - 3"	STK - Standard S3 - ANSI FL - Full Lip radius	626 605 613	0B - non-IC Zero Bitted KA - non-IC keyed alike KD - non-IC keyed different OEM - non-IC OEM cylinder RL - Radius latch

Series	
BEST	STANLEY
5K	QTL2

Core Housing	
BEST	STANLEY
0	Choose 20, 30, or 40 Function
6	Choose 50, 60, or 70 Function with SC in Keyway
7	Choose 51, 61, or 71 Function

Function	
BEST	STANLEY
A	50 or 51
D	70 or 71
L	40
N	30
R	60 or 61
1DT	20

Lever Style	
BEST	STANLEY
14	M
15	E

QTL200 trim is 3" diameter

Strike	
BEST	STANLEY
STK	118F
S3	478S
FL	FLR

Finish	
BEST	STANLEY
626	626
605	605
613	613

Options	
BEST	STANLEY
0B	ZB
KA	KA
KD	KD
OEM	LC
RL	RA

Series	Function	Design	Finish	Latch	Strike	Keyway	# of Pins	Keying
QTL2	20 - Single Dummy 30 - Passage 40 - Privacy 50 - Entry/Office 51 - Entry/Office SFIC 60 - Classroom 61 - Classroom SFIC 70 - Storeroom 71 - Storeroom SFIC	E - Sierra M - Summit A - Slate	605 - Bright Brass 613 - Oil Rubbed Bronze 619 - Satin Nickel 625 - Bright Chrome 626 - Satin Chrome	RA - Adjustable Radius SA - Adjustable Square NO - No Latch	478S - ANSI 4-7/8" x 1-1/4" 118F - ANSI 1-1/8" x 2-3/4" FLS - Full Lip Square corner FLR - Full Lip Round corner NOS - No Strike	BF - BEST "F" SFIC KW - Kwikset WE - Weiser SC - Schlage GA - Yale "GA" LA - Sargent "LA" LC - Less Cylinder	6 - 6-pin (non-IC or SFIC) 7 - 7-pin (SFIC only)	KD - Keyed Different KA - Keyed Alike SK - Special Keying ZB - Zero Bitted