

6 Series Centerline Strikes
BES-S65U (Standard Profile Universal)
BES-L65U (Low Profile Universal)
BES-S65ULMKM (Standard Profile Universal with Monitoring)
BES-L65ULMKM (Low Profile Universal with Monitoring)

The BEST 6 Series Electric Strikes offer two profile designs to accommodate various latch projections.

Best's "all-in-one" 6 Series electric strike combines several requested key features. Standard features include a multi-voltage single solenoid, selectable lock mode (no tools necessary), horizontal adjustment, and plug-in wire connectors. An optional monitor switch is also available.

The L65 Low Profile version accepts 1/2" or 5/8" latch projection (perfect for narrow stile aluminum frames). The S65 Standard version is ideal when you require 3/4" latch projection.

Not only will installations be faster and easier, distributors and installers can cut their strike inventory significantly, because one strike does it all!



Energy 375mA¹ Field-Selectable 12/24VDC, 12-24VAC



Strength 1500lbf Static² 70ft-lb Dynamic



Monitoring
Optional Latch & Keeper
Monitor Models Available



Endurance 500,000 Cycles²



Warranty Three-year (Limited)



ModeField-Selectable
Fail-Secure & Fail-Safe

One strike for all your needs.

Not only will installations be faster and easier, you can cut your strike inventory significantly, because one strike does it all!

Product specifications					
Construction	Stainless steel				
Door lock type	Cylindrical and narrowline aluminum				
Frame type	Hollow metal, aluminum and wood				
Latch projection	Standard profile accommodates 3/4" (19mm) and low-profile accommodates 1/2" (12.7mm) or 5/8" (16mm) latch projections				
Connectors	Plug-in wire				
Handing	Non-handed				
Optional accessories	BES-LEKS601 1" lip extension kit for retrofit applications, black finish (for Standard profile) BES-LEKS602 2" lip extension kit for retrofit applications, black finish (for Standard profile) BES-LEKS603 3" lip extension kit for retrofit applications, black finish (for Standard profile) BES-SMT-01 Strike marketing template kit, aluminum				
Finishes	32D Brushed Stainless Steel				
Warranty	Three-year limited				
Certifications	UL 1034 burglary resistant Listed UL 294 Listed for Access Control Unit Accessory (6th Edition) Certified to ANSI/BHMA standard A156.31, Grade 1, endurance 500,000 cycles ²				

Model	Mode	Volts*	Duty	Amps
BES-S65U*	Field-selectable Fail Secure or Fail Safe	12VDC	Continuous	.375
BES-L65U*		NA	NA	NA
BES-S65ULMKM*		24VDC	Continuous	.19
BES-L65ULMKM*		12 thru 24 VAC	Intermittent	.280565

Intermittent Duty=energized less than 1 min. with duty ratio 1:5, Continuous Duty=energized 1 min. or more. *Field selectable voltage

Features

BEST Centerline Strikes

- Standard profile accommodates: 3/4" (19mm) and Low-profile accommodates 1/2" (12.7mm) or 5/8" (16mm) latch projections
- Horizontal adjustment: 1/4" (6.4mm)
- Non-handed
- **Trim plate:** included to cover up irregular frame cutout
- **Patents:** US patent 6,874,830, US patent 7,144,053 and Canadian patent 2,405,642
- Warranty: three-year limited

Frame Type







Door Lock Type





Choose BEST Rim Strikes for a solution that you can trust.



112VDC

²Grade 1, BHMA 04 & 14 faceplates. Grade 2, 1,000lbf static 07 & 08 faceplates.