



4 Series Centerline Strikes

BES-4105U (Fail Secure 12VAC/VDC Universal)

BES-4108U (Fail Secure 24VAC/VDC Universal)

BES-4306U (Fail Safe 12VDC Universal)

BES-4309U (Fail Safe 24VDC Universal)

BES-F41045 (Fire-Rated, Fail Secure 4 Faceplate 12VAC/VDC)

BES-F41048 (Fire-Rated, Fail Secure 4 Faceplate 24VAC/VDC)

BES-F41145 (Fire-Rated, Fail Secure 14 Faceplate 12VAC/VDC)

BES-F41148 (Fire-Rated, Fail Secure 14 Faceplate 24VAC/VDC)



The BEST 4 Series Electric Strikes have earned their reputation as durable, reliable and economical means of controlling access.

Unique anti-vibration design prevents manipulation by vibration.

Crossed wires are never a problem, as the coil is non polarity-conscious.

The F4 Series Electric Strikes are BEST's answer to the need for extra strength in heavy-duty applications and are fire labeled.



Energy
200mA¹ 12VAC/VDC,
24VAC/VDC



Fire-Rated
Optional 1-1/2-Hour
Models Available²



Strength
1500lb Static³
70ft-lb Dynamic



Endurance
500,000 Cycles⁴



Warranty
Three-year (Limited)



Mode
Fail-Secure & Fail-Safe

Heavy duty for high-traffic environments.

These commercial-duty strikes are ideal for office complexes, industrial buildings, schools, hospitals, retail outlets and other commercial centers.

Product specifications	
Construction	Stainless steel
Door lock type	Cylindrical and narrowline aluminum
Frame type	Hollow metal, aluminum and wood
Latch projection	3/4" (19mm)
Connectors	Screw terminals
Handing	Non-handed
Optional accessories*	BES-LEK01 1" lip extension kit for retrofit applications, black finish BES-LEK02 2" lip extension kit for retrofit applications, black finish BES-LEK03 3" lip extension kit for retrofit applications, black finish
Finishes	32D Brushed Stainless Steel
Warranty	Three-year limited
Certifications	UL 1034 burglary-resistant Listed UL 10C, 1-1/2-hour fire-rating Listed ² CANULC S104, 1-1/2-hour fire-rating Listed ² Certified to ANSI/BHMA standard A156.31, Grade 1, endurance 500,000 cycles ⁴

Model	Mode	Volts	Duty	Amps AC	Amps DC
BES-4105U [†]	Fail Secure	12VAC/VDC	Intermittent Continuous	.15	.20
BES-4108U [†]		24VAC/VDC		.07	.11
BES-4306U [†]	Fail Safe	12VDC	Continuous	NA	.20
BES-4309U [†]		24VDC		NA	.11
BES-F41045	Fail Secure	12VAC/VDC	Intermittent Continuous	.15	.20
BES-F41048		24VAC/VDC		.07	.11
BES-F41145		12VAC/VDC		.15	.20
BES-F41148		24VAC/VDC		.07	.11

*Optional accessories do not work with fire rated F4 models.

[†]Universal kit including 4 faceplates

NOTE: Intermittent Duty = Energized less than 1 min. Continuous Duty = Energized 1 min. or more. Duty Ratio 1:5.



¹At 12VDC

²Fire-rated (F) models only available in fail-secure mode with 04 & 14 faceplates.

³1,500lb Static for fire-rated models, 1,000lb for non-fire-rated 04 & 14 faceplates, 500lb for 07 & 08 faceplates.


⁴Fire-rated (F) models only, 250,000 for other models

Features


BEST Centerline Strikes

- **Accommodates:** 3/4" (19mm) latch projection
- **1-1/2" (38mm) cut-out depth:** accommodates most door frame material types
- **Use with:** wide range of door thicknesses, 1-3/8" (35mm) to 2-3/8" (60mm)
- **Includes:** standard mounting tabs and fasteners
- **Non-handed**
- **Trim plate:** included to cover up irregular frame cutout
- **Warranty:** three-year limited


Frame Type



Hollow Metal



Aluminum




Wood

Door Lock Type



Cylindrical



Narrowline
Aluminum

Choose BEST Rim Strikes for a solution that you can trust.

bestaccess.com

dormakaba

BEST is a trademark of dormakaba USA Inc. All rights reserved.



BA-0337

© 2018 dormakaba USA Inc.